EMBLEM Solvent Clear Film

EMBLEM SOCF is a glossy clear film with one-side coating for solvent and eco-solvent inks. The print is waterproof with brilliant colours.

Matchcode:	SOCF
Material:	Polyester
Finish:	glossy
Colour:	clear
Thickness:	195µ
Width of rolls:	42″
Length of rolls:	35 meters
Flame retardant:	no

COMPATIBLE INKS:

Eco Solvent:	yes	UV:	yes
Solvent:	yes	Latex:	yes

Different printers, inks, resolutions and printing qualities result into numerous different printing parameters. In addition, there a numerous factors influencing processing and the application of our materials. For this reason, we cannot make specific statements as to drying times and maximum ink absorption. For this reason, we recommend you to perform own tests in order to verify the desired results. Our product specifications are not to be understood as legally binding guarantees assuring specific characteristics. Any liabilities and guarantees, as well as claims for compensation beyond the value of the product itself are excluded.

DATAPLOT SINCE 1979

Gutenbergstraße 15 · D-24558 Henstedt-Ulzburg · Telefon: +49 4193-9950 · Telefax: +49 4193-995220
E-Mail: info@dataplot.de · Internet: www.dataplot.de

EMBLEM-Datenblätter Solvent en way; Geändert: 23.07.13

EMBLEM Solvent Clear Film

Description:

EMBLEM SOCF is a glossy clear film with one-side coating for solvent and eco-solvent inks. The print is waterproof with brilliant colours.
This special film is laying flat

Processing:

The drying of the printed medium is highly dependent on the inks used as well as the solvent coating and the colour saturation. We recommend not to print in a roll-to-roll process. Using high volume of inks may cause drying time of 2 to 3 days.

Solvent residues due to insufficient drying times can lead to blocking during transport in rolled-up form. During lamination such residues can negatively impact flatness, the shrinkage behaviour and the anchorage of the laminate on the printed film.

We recommend to protect the printed surface if it is subject to abrasion, sweat or other mechanical influences. In this case we recommend to protect the image with laminating film.

To avoid fingerprints the use of cotton-gloves is advisable.

Application:

glass-decoration, exhibitions, backlit